

Safety Data Sheet

Copyright, 2014, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 27-3508-2
 Version Number:
 4.00

 Issue Date:
 08/19/14
 Supercedes Date:
 05/24/13

SECTION 1: Identification

1.1. Product identifier

3M(TM) Fire Barrier Sealant FD 150+, Red

Product Identification Numbers

98-0400-5598-4, 98-0400-5599-2, 98-0400-5600-8, 98-0400-5601-6

1.2. Recommended use and restrictions on use

Recommended use

Fire Protection, Caulk used as a passive fire protection.

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Industrial Adhesives and Tapes Division ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Skin Corrosion/Irritation: Category 2.

Skin Sensitizer: Category 1A. Carcinogenicity: Category 1A.

Specific Target Organ Toxicity (single exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms





Hazard Statements

Causes skin irritation. May cause an allergic skin reaction. May cause cancer.

Causes damage to organs: cardiovascular system | nervous system | kidney/urinary tract | respiratory system |

Precautionary Statements

General:

Keep out of reach of children.

If medical advice is needed, have product container or label at hand.

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe vapors.

Wear protective gloves.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF exposed: Call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/attention. Specific treatment (see Notes to Physician on this label).

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Notes to Physician:

This product contains ethylene glycol. Effects of oral ethylene glycol poisoning can be divided into three stages which generally occur over a time-course of hours to days following ingestion: Stage 1 (neurological effects), stage 2 (cardiopulmonary effects) and stage 3 (renal effects). If ethylene glycol poisoning is confirmed, intravenous (IV) administration of ethanol should be considered. Additional pharmacologic and supportive care should be based on the treating physician's judgement.

2.3. Hazards not otherwise classified

None.

10% of the mixture consists of ingredients of unknown acute oral toxicity.

31% of the mixture consists of ingredients of unknown acute dermal toxicity.

41% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|---|---------------|--------------------------|
| Calcium Carbonate | 1317-65-3 | 40 - 70 Trade Secret * |
| Polymer NJTS Reg. No. 04499600-7187 | Trade Secret* | 10 - 30 Trade Secret * |
| Acrylic Emulsion | 70677-00-8 | 5 - 10 Trade Secret * |
| Water | 7732-18-5 | 5 - 10 Trade Secret * |
| Mineral Spirits | 64742-88-7 | 5 - 10 Trade Secret * |
| Iron Oxide | 1309-37-1 | 1 - 5 Trade Secret * |
| Ethylene Glycol | 107-21-1 | 1 - 5 Trade Secret * |
| Plasticizer | 27138-31-4 | 1 - 5 Trade Secret * |
| Ethyl hydroxyethyl cellulose | 9004-58-4 | 0.5 - 1.5 Trade Secret * |
| Quartz Silica | 14808-60-7 | 0.1 - 1 Trade Secret * |
| 5-Chloro-2-Methyl-4-Isothiazoline-3-one | 26172-55-4 | < 0.1 Trade Secret * |
| 2-Methyl-4-Isothiazoline-3-one | 2682-20-4 | < 0.1 Trade Secret * |

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

This product contains ethylene glycol. Effects of oral ethylene glycol poisoning can be divided into three stages which generally occur over a time-course of hours to days following ingestion: Stage 1 (neurological effects), stage 2 (cardiopulmonary effects) and stage 3 (renal effects). If ethylene glycol poisoning is confirmed, intravenous (IV) administration of ethanol should be considered. Additional pharmacologic and supportive care should be based on the treating physician's judgement.

SECTION 5: Fire-fighting measures

Page 3 of 13

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|-------------------|------------|--------|-------------------------------|----------------------------|
| Ethylene Glycol | 107-21-1 | ACGIH | CEIL(as aerosol):100 mg/m3 | A4: Not class. as human |
| | | | | carcin |
| Ethylene Glycol | 107-21-1 | CMRG | CEIL(as vapor and | |
| | | | aerosol):100 mg/m3 | |
| Iron Oxide | 1309-37-1 | OSHA | TWA(as fume):10 mg/m3 | |
| Iron Oxide | 1309-37-1 | ACGIH | TWA(respirable fraction):5 | A4: Not class. as human |
| | | | mg/m3 | carcin |
| Calcium Carbonate | 1317-65-3 | OSHA | TWA(as total dust):15 | |
| | | | mg/m3;TWA(respirable | |
| | | | fraction):5 mg/m3 | |
| Quartz Silica | 14808-60-7 | OSHA | TWA concentration(as total | |
| | | | dust):0.3 mg/m3;TWA | |
| | | | concentration(respirable):0.1 | |

| | | | mg/m3(2.4 millions of | |
|--------------------------------|------------|-------|---------------------------|---------------------|
| | | | particles/cu. ft.) | |
| Quartz Silica | 14808-60-7 | ACGIH | TWA(respirable | A2: Suspected human |
| | | | fraction):0.025 mg/m3 | carcin. |
| 5-Chloro-2-Methyl-4- | 26172-55-4 | CMRG | TWA:0.076 mg/m3;STEL:0.23 | Sensitizer |
| Isothiazoline-3-one | | | mg/m3 | |
| 2-Methyl-4-Isothiazoline-3-one | 2682-20-4 | CMRG | TWA:1.5 mg/m3;STEL:4.5 | Sensitizer |
| | | | mg/m3 | |
| Mineral Spirits | 64742-88-7 | CMRG | TWA:100 ppm | |

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form: Specific Physical Form: Paste

Odor, Color, Grade: Red paste with low odor No Data Available Odor threshold Melting point No Data Available Flash Point No flash point

Flammability (solid, gas) Not Classified Flammable Limits(LEL) Not Applicable Flammable Limits(UEL) Not Applicable

1.45 [*Ref Std:* WATER=1] **Specific Gravity**

Solubility- non-water No Data Available **Autoignition temperature** Not Applicable **Decomposition temperature** No Data Available **Volatile Organic Compounds** < 15 % weight **VOC Less H2O & Exempt Solvents** < 250 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance Condition Carbon monoxide Not Specified Not Specified Carbon dioxide

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause target organ effects after inhalation.

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause target organ effects after ingestion.

Target Organ Effects:

Single exposure may cause:

Cardiac Effects: Signs/symptoms may include irregular heartbeat (arrhythmia), changes in heart rate, damage to heart muscle, heart attack, and may be fatal.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

| Ingredient | C.A.S. No. | Class Description | Regulation |
|----------------------|------------|--------------------------------|---|
| SILICA, CRYS AIRRESP | 14808-60-7 | Known human carcinogen | National Toxicology Program Carcinogens |
| Quartz Silica | 14808-60-7 | Grp. 1: Carcinogenic to humans | International Agency for Research on Cancer |

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|-------------------------------------|-------------|---------|---|
| Overall product | Dermal | | No data available; calculated ATE > 5,000 mg/kg |
| Overall product | Inhalation- | | No data available; calculated ATE > 50 mg/l |
| | Vapor(4 hr) | | |
| Overall product | Ingestion | | No data available; calculated ATE > 5,000 mg/kg |
| Calcium Carbonate | Dermal | Rat | LD50 > 2,000 mg/kg |
| Calcium Carbonate | Inhalation- | Rat | LC50 3.0 mg/l |
| | Dust/Mist | | |
| | (4 hours) | | |
| Calcium Carbonate | Ingestion | Rat | LD50 6,450 mg/kg |
| Polymer NJTS Reg. No. 04499600-7187 | Ingestion | Rat | LD50 > 2,000 mg/kg |
| Mineral Spirits | Inhalation- | | LC50 estimated to be 20 - 50 mg/l |
| | Vapor | | |
| Mineral Spirits | Dermal | Rabbit | LD50 > 3,000 mg/kg |
| Mineral Spirits | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Plasticizer | Dermal | Rat | LD50 > 2,000 mg/kg |
| Plasticizer | Inhalation- | Rat | LC50 > 200 mg/l |
| | Dust/Mist | | |
| | (4 hours) | | |
| Plasticizer | Ingestion | Rat | LD50 3,295 mg/kg |

| Iron Oxide | Dermal | Not | LD50 3,100 mg/kg |
|---|-------------|-----------|------------------------------------|
| | | available | |
| Iron Oxide | Ingestion | Not | LD50 3,700 mg/kg |
| | | available | |
| Ethylene Glycol | Ingestion | Human | LD50 1,600 mg/kg |
| Ethylene Glycol | Inhalation- | Other | LC50 estimated to be 5 - 12.5 mg/l |
| | Dust/Mist | | |
| | (4 hours) | | |
| Ethylene Glycol | Dermal | Rabbit | 9,530 mg/kg |
| Ethyl hydroxyethyl cellulose | Ingestion | Rat | LD50 > 10,000 mg/kg |
| Quartz Silica | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Quartz Silica | Ingestion | | LD50 estimated to be > 5,000 mg/kg |
| 2-Methyl-4-Isothiazoline-3-one | Dermal | Rabbit | LD50 87 mg/kg |
| 5-Chloro-2-Methyl-4-Isothiazoline-3-one | Dermal | Rabbit | LD50 87 mg/kg |
| 2-Methyl-4-Isothiazoline-3-one | Inhalation- | Rat | LC50 0.33 mg/l |
| | Dust/Mist | | |
| | (4 hours) | | |
| 2-Methyl-4-Isothiazoline-3-one | Ingestion | Rat | LD50 40 mg/kg |
| 5-Chloro-2-Methyl-4-Isothiazoline-3-one | Inhalation- | Rat | LC50 0.33 mg/l |
| · | Dust/Mist | | |
| | (4 hours) | | |
| 5-Chloro-2-Methyl-4-Isothiazoline-3-one | Ingestion | Rat | LD50 40 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---|---------|---------------------------|
| Calcium Carbonate | Rabbit | No significant irritation |
| Polymer NJTS Reg. No. 04499600-7187 | Rabbit | Minimal irritation |
| Mineral Spirits | Rabbit | Irritant |
| Plasticizer | Rabbit | No significant irritation |
| Iron Oxide | Rabbit | No significant irritation |
| Ethylene Glycol | Rabbit | Minimal irritation |
| Ethyl hydroxyethyl cellulose | | Minimal irritation |
| Quartz Silica | | No significant irritation |
| 2-Methyl-4-Isothiazoline-3-one | Rabbit | Corrosive |
| 5-Chloro-2-Methyl-4-Isothiazoline-3-one | Rabbit | Corrosive |

Serious Eye Damage/Irritation

| Serious Eye Dumuge, minution | | |
|---|---------|---------------------------|
| Name | Species | Value |
| Calcium Carbonate | Rabbit | No significant irritation |
| Polymer NJTS Reg. No. 04499600-7187 | | Mild irritant |
| Mineral Spirits | Rabbit | No significant irritation |
| Plasticizer | Rabbit | No significant irritation |
| Iron Oxide | Rabbit | No significant irritation |
| Ethylene Glycol | Rabbit | Mild irritant |
| Ethyl hydroxyethyl cellulose | | Mild irritant |
| 2-Methyl-4-Isothiazoline-3-one | Rabbit | Corrosive |
| 5-Chloro-2-Methyl-4-Isothiazoline-3-one | Rabbit | Corrosive |

Skin Sensitization

| Name | Species | Value |
|---|---------|--|
| Mineral Spirits | Guinea | Not sensitizing |
| - | pig | |
| Plasticizer | Guinea | Not sensitizing |
| | pig | |
| Iron Oxide | Human | Some positive data exist, but the data are not |
| | | sufficient for classification |
| Ethylene Glycol | Human | Some positive data exist, but the data are not |
| | | sufficient for classification |
| 2-Methyl-4-Isothiazoline-3-one | Human | Sensitizing |
| | and | |
| | animal | |
| 5-Chloro-2-Methyl-4-Isothiazoline-3-one | Human | Sensitizing |
| | and | |
| | animal | |

Photosensitization

| Name | Species | Value |
|---|---------|-----------------|
| 2-Methyl-4-Isothiazoline-3-one | Human | Not sensitizing |
| | and | |
| | animal | |
| 5-Chloro-2-Methyl-4-Isothiazoline-3-one | Human | Not sensitizing |
| | and | |
| | animal | |

Respiratory Sensitization

| Name | Species Value |
|------|---------------|
|------|---------------|

Germ Cell Mutagenicity

| Name | Route | Value |
|---|----------|--|
| Mineral Spirits | In vivo | Not mutagenic |
| Mineral Spirits | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Plasticizer | In Vitro | Not mutagenic |
| Iron Oxide | In Vitro | Not mutagenic |
| Ethylene Glycol | In Vitro | Not mutagenic |
| Ethylene Glycol | In vivo | Not mutagenic |
| Quartz Silica | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Quartz Silica | In vivo | Some positive data exist, but the data are not sufficient for classification |
| 2-Methyl-4-Isothiazoline-3-one | In vivo | Not mutagenic |
| 2-Methyl-4-Isothiazoline-3-one | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| 5-Chloro-2-Methyl-4-Isothiazoline-3-one | In vivo | Not mutagenic |
| 5-Chloro-2-Methyl-4-Isothiazoline-3-one | In Vitro | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name | Route | Species | Value |
|---|------------|-------------------------------|--|
| Mineral Spirits | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Mineral Spirits | Inhalation | Human and animal | Some positive data exist, but the data are not sufficient for classification |
| Iron Oxide | Inhalation | Human | Some positive data exist, but the data are not sufficient for classification |
| Ethylene Glycol | Ingestion | Multiple animal species | Not carcinogenic |
| Quartz Silica | Inhalation | Human and animal | Carcinogenic |
| 2-Methyl-4-Isothiazoline-3-one | Dermal | Mouse | Not carcinogenic |
| 2-Methyl-4-Isothiazoline-3-one | Ingestion | Rat | Not carcinogenic |
| 5-Chloro-2-Methyl-4-Isothiazoline-3-one | Dermal | Mouse | Not carcinogenic |
| 5-Chloro-2-Methyl-4-Isothiazoline-3-one | Ingestion | Rat | Not carcinogenic |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|-------------------|------------|--------------------------|---------|------------------------|------------------------------|
| Calcium Carbonate | Ingestion | Not toxic to development | Rat | NOAEL 625 mg/kg/day | premating & during gestation |
| Mineral Spirits | Inhalation | Not toxic to development | Rat | NOAEL 2.4 mg/l | during organogenesi |

| | | | | | S |
|---|------------|--|-------------------------------|-----------------------------|-----------------------------|
| Plasticizer | Ingestion | Not toxic to female reproduction | Rat | NOAEL 500 mg/kg/day | 2 generation |
| Plasticizer | Ingestion | Not toxic to male reproduction | Rat | NOAEL 400 mg/kg/day | 2 generation |
| Plasticizer | Ingestion | Some positive developmental data exist, but the data are not sufficient for classification | Rat | NOAEL 1,000 mg/kg/day | during gestation |
| Ethylene Glycol | Ingestion | Not toxic to female reproduction | Multiple animal species | NOAEL 1,000 mg/kg/day | 2 years |
| Ethylene Glycol | Ingestion | Not toxic to male reproduction | Multiple animal species | NOAEL 1,000 mg/kg/day | 2 years |
| Ethylene Glycol | Dermal | Some positive developmental data exist, but the data are not sufficient for classification | Mouse | NOAEL 3,549 mg/kg/day | during organogenesi s |
| Ethylene Glycol | Ingestion | Some positive developmental data exist, but the data are not sufficient for classification | Mouse | LOAEL 750 mg/kg/day | during organogenesi s |
| Ethylene Glycol | Inhalation | Some positive developmental data exist, but the data are not sufficient for classification | Mouse | NOAEL 1,000 mg/kg/day | during organogenesi s |
| 2-Methyl-4-Isothiazoline-3-one | Ingestion | Not toxic to female reproduction | Rat | NOAEL 10 mg/kg/day | 2 generation |
| 2-Methyl-4-Isothiazoline-3-one | Ingestion | Not toxic to male reproduction | Rat | NOAEL 10 mg/kg/day | 2 generation |
| 2-Methyl-4-Isothiazoline-3-one | Ingestion | Not toxic to development | Rat | NOAEL 15 mg/kg/day | during organogenesi s |
| 5-Chloro-2-Methyl-4-Isothiazoline-3-one | Ingestion | Not toxic to female reproduction | Rat | NOAEL 10 mg/kg/day | 2 generation |
| 5-Chloro-2-Methyl-4-Isothiazoline-3-one | Ingestion | Not toxic to male reproduction | Rat | NOAEL 10 mg/kg/day | 2 generation |
| 5-Chloro-2-Methyl-4-Isothiazoline-3-one | Ingestion | Not toxic to development | Rat | NOAEL 15 mg/kg/day | during organogenesi s |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|------------------------------------|------------|--|--|------------------------------|------------------------|---------------------------|
| Calcium Carbonate | Inhalation | respiratory system | All data are negative | Rat | NOAEL 0.812 mg/l | 90 minutes |
| Mineral Spirits | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human and animal | NOAEL Not available | |
| Mineral Spirits | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |
| Mineral Spirits | Inhalation | nervous system | Some positive data exist, but the data are not sufficient for classification | Dog | NOAEL 6.5 mg/l | 4 hours |
| Ethylene Glycol | Ingestion | heart nervous system kidney and/or bladder respiratory system | Causes damage to organs | Human | NOAEL Not available | poisoning and/or abuse |
| Ethylene Glycol | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | poisoning and/or abuse |
| Ethylene Glycol | Ingestion | liver | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | poisoning and/or abuse |
| 2-Methyl-4-Isothiazoline- 3-one | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |
| 5-Chloro-2-Methyl-4- | Inhalation | respiratory irritation | Some positive data exist, but the | similar | NOAEL Not | |

| Isothiazoline-3-one | | data are not sufficient for | health | available | |
|---------------------|--|-----------------------------|---------|-----------|--|
| | | classification | hazards | | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|-------------------|------------|---|--|-------------------------------|------------------------------|-----------------------|
| Calcium Carbonate | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | occupational exposure |
| Mineral Spirits | Inhalation | nervous system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 4.6 mg/l | 6 months |
| Mineral Spirits | Inhalation | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 1.9 mg/l | 13 weeks |
| Mineral Spirits | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Multiple animal species | NOAEL 0.6 mg/l | 90 days |
| Mineral Spirits | Inhalation | bone, teeth, nails, and/or hair blood liver muscles | All data are negative | Rat | NOAEL 5.6 mg/l | 12 weeks |
| Mineral Spirits | Inhalation | heart | All data are negative | Multiple animal species | NOAEL 1.3 mg/l | 90 days |
| Plasticizer | Ingestion | hematopoietic system liver | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 2,500 mg/kg/day | 90 days |
| Iron Oxide | Inhalation | pulmonary fibrosis pneumoconiosis | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | occupational exposure |
| Ethylene Glycol | Ingestion | kidney and/or bladder vascular system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 200 mg/kg/day | 2 years |
| Ethylene Glycol | Ingestion | heart hematopoietic system liver immune system muscles | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 1,000 mg/kg/day | 2 years |
| Ethylene Glycol | Ingestion | respiratory system | Some positive data exist, but the data are not sufficient for classification | Mouse | NOAEL 12,000 mg/kg/day | 2 years |
| Ethylene Glycol | Ingestion | skin endocrine system bone, teeth, nails, and/or hair nervous system eyes | All data are negative | Multiple animal species | NOAEL 1,000 mg/kg/day | 2 years |
| Quartz Silica | Inhalation | silicosis | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

| ······································ | | | | | |
|--|-------------------|--|--|--|--|
| Name | Value | | | | |
| Mineral Spirits | Aspiration hazard | | | | |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Test Organism Test Type Result Water flea, Daphnia magna 48 hours Effect Level 50% 96.5 mg/l

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <u>http://3M.com/Transportinfo</u> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

 Ingredient
 C.A.S. No
 % by Wt

 Ethylene Glycol
 107-21-1
 1 - 5

15.2. State Regulations

Contact 3M for more information.

California Proposition 65

IngredientC.A.S. No.ClassificationSILICA, CRYSTALLINE (AIRBORNENoneCarcinogenPARTICLES OF RESPIRABLE SIZE)

WARNING: This product contains a chemical known to the State of California to cause cancer.

15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

Page 12 of 13

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 0 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 2 Flammability: 0 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® III) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® III ratings are to be used with a fully implemented HMIS® III program. HMIS® is a registered mark of the American Coatings Association (ACA).

 Document Group:
 27-3508-2
 Version Number:
 4.00

 Issue Date:
 08/19/14
 Supercedes Date:
 05/24/13

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com

Page 13 of 13