

Effast ABS Cement Issue 12.07.12

## 1. Identification of the Substance/Preparation and the Company Undertaking

Product Name Effast ABS Cement

Supplier Bostik Ltd

Common Road Stafford Staffordshire ST16 3EH

Tel: 01785 272625

Emergency Telephone Tel. 01785 272650

Application Adhesive

### 2. Hazard Identification

## **Hazard Description**





nt Highly Flammable

### Information concerning particular hazards to man and environment

Irritating to eyes

Repeated exposure may cause skin dryness or cracking

Vapours may cause drowsiness and dizziness

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

## **Classification System**

R11 Highly Flammable

R36 Irritating to eyes

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment

R66 Repeated exposure may cause skin dryness or cracking

R67 Vapours may cause drowsiness and dizziness

## 3. Composition/Information on Ingredients

Name	EINECS	CAS-No.	Content	Classification	Risk Phrase(s)
	No.				
2-2-heptadec-8-enyl-2-imidazolin-1-yl) ethanol	-	95-38-5	<1%	Xn, C, N	R22, R34, R50/53
Butanone	201-159-0	78-93-3	60-100%	F, Xi	R11, R36, R66, R67

For wording of the listed Risk Phrase(s) refer to section 15

MSDS 431.1 Page 1 of 7



Effast ABS Cement Issue 12.07.12

#### 4. First Aid Measures

### In the event of exposure by inhalation

Remove victim from source of exposure Move the exposed person to fresh air at once Get medical attention

### In the event of splashes or contact with eyes

Rinse the eye with water immediately Continue to rinse for 15 minutes and get medical attention

## In the event of splashes or contact with skin

Promptly flush contaminated skin with water Promptly remove clothing if soaked through and flush skin with water Wash skin with soap and water Get medical attention if irritation persists after washing

### In the event of swallowing

DO NOT induce vomiting Get medical attention immediately

### 5. Fire Fighting Measures

### **Extinguishing Media**

Extinguish with Foam, Carbon Dioxide, Dry Powder

### Specific Hazards

Toxic gases/vapours/fumes of Caron dioxide (CO2), Carbon monoxide (CO)

## **Special Protective Equipment for Fire Fighters**

Self contained breathing apparatus and full protective clothing must be worn in case of fire

### 6. Accidental Release Measures

#### **Personal Precautions**

Avoid contact with skin and eyes Provide adequate ventilation

Wear protective clothing as described in section 8 of this safety sheet

## **Environmental Precautions**

Prevent entry to drains and discharge into water courses

### Methods for Cleaning up

Stop leak if possible without taking risks

Remove all ignition sources

Avoid sparks, flames, heat and smoking

Ventilate area

Absorb with sand or other inert absorbent

Collect with absorbent non-combustible material into suitable containers

Containers with collected spillage must be properly labelled with correct contents and hazard symbols

MSDS 431.1 Page 2 of 7



Effast ABS Cement Issue 12.07.12

## 7. Handling and Storage

### **Usage Precautions**

Keep away from heat, sparks and open flame Avoid spilling, skin and eye contact Ventilate well, avoid breathing vapours Use approved respirator if air contamination is above accepted level

# Storage Precautions

Flammable/combustible – Keep away from oxidisers, heat and flames Ground containers and transfer equipment to eliminate static electric sparks Store at a moderate temperature in dry, well ventilated area

### Storage Class

Flammable liquid storage

### 8. Exposure Control/Personal Protection

#### **Exposure Limit Values**

Name	Std	TWA – 8 hrs		STEL – 15 min	
Butanone	WEL	200 ppm(Sk)	600 mg/m3(Sk)	300 ppm(Sk)	899 mg/m3(Sk)

WEL = Workplace Exposure Limit

### **Protective Equipment**









### **Engineering Equipment**

Explosion-proof general and local exhaust ventilation

### **Respiratory Equipment**

Respiratory equipment must be used if air contamination exceeds acceptable level Wear mask supplied with: Gas cartridge suitable for organic substances

## **Hand Protection**

Protective gloves must be worn if there is a risk of direct contact or splash. Use protective gloves made of: Nitrile.
Use thin cotton gloves inside rubber gloves if allergy risk

#### **Eve Protection**

Wear splash-proof goggles to prevent any possibility of eye contact

### Other Protection

Wear appropriate clothing to prevent repeated or prolonged skin contact

### **Hygiene Measures**

DO NOT SMOKE IN THE WORK AREA!

Wash promptly if skin becomes contaminated

Wash at the end of each work shift and before eating, smoking and using the toilet Use appropriate skin cream to prevent drying of skin

MSDS 431.1 Page 3 of 7



Effast ABS Cement Issue 12.07.12

## 9. Physical and Chemical Properties

Appearance Liquid

Colour Colourless

Odour Solvent

**Solubility** Slightly soluble water

Flash Point (°C) -4

Relative Density 0.875 @ 25°C

### 10. Stability and Reactivity

#### Stability

Avoid: Heat, sparks, flames

#### Materials to avoid

Strong oxidising substances

## **Hazardous decomposition products**

Fire or high temperatures create: Carbon Dioxide (CO2), Carbon Monoxide (CO)

## 11. Toxicological Information

## Inhalation

Drowsiness, dizziness, disorientation, vertigo

### **Skin Contact**

Prolonged contact may cause dryness of the skin

## **Eye Contact**

Irritating to eyes

### 12. Ecological Information

#### **Ecotoxicity**

The product contains a substance which is harmful aquatic organisms and may cause long term adverse effects in the aquatic environment

## 13. Disposal Considerations

### **General Information**

Waste is classified as hazardous waste

Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority

### **Disposal Methods**

Dispose of waste and residues in accordance with local authority requirements.

MSDS 431.1 Page 4 of 7



Effast ABS Cement Issue 12.07.12

## 13. Disposal Considerations (continued)

Do not allow runoff to sewer, waterway or ground Recover and reclaim or recycle, if practical

## **Waste Class**

Classified as Special Waste. Not permitted for landfill in liquid state

## 14. Transport Information



UK Road Class	3		
Proper Shipping Name	ADHESIVE		
UN No. Road	1133	UK Road Pack GR.	III
ADR Class No	3	ADR Class	Class 3 Flammable liquids
ADR Pack Group	III	Tunnel Restriction Code	(D/E)
Hazard No. (ADR)	33	ADR Label No.	3
HAZCHEM Code	3YE	CEFIC Tec(R) No.	30GF1-III, 30GF1-sp
RID Class No.	3	RID Pack Group	III
UN No. Sea	1133	IMDG Class	3
IMDG Pack Gr.	III	EMS	F-E, S-D
MFAG	See Guide	UN No. Air	1133
Air Class	3	Air Pack Gr.	III

MSDS 431.1 Page 5 of 7



Effast ABS Cement Issue 12.07.12

## 15. Regulatory Information

## Labelling





### **Risk Phrases**

R11 Highly Flammable

R36 Irritating to eyes

R52/53 Harmful to aquatic organisms, may cause long-term adverse

effects in the aquatic environment

## **Safety Phrases**

S2 Keep out of the reach of child	dren
-----------------------------------	------

S9 Keep container in a well-ventilated place

S16 Keep away from sources of ignition – No smoking

S26 In case of contact with eyes, rinse immediately with plenty of

water and seek medical advice

S36/37/39 Wear suitable protective clothing, gloves and eye/face protection

S46 If swallowed, seek medical advice immediately and show this

container or label

S51 Use only in well-ventilated areas

S60 This material and its container must be disposed of as

hazardous waste

## **Statutory Instruments**

Chemicals (Hazardous Information and Packaging) Regulations. Control of Substances Hazardous to Health

### **Approved Code of Practice**

Classification and Labelling of Substances and Preparations Dangerous for Supply

MSDS 431.1 Page 6 of 7



Effast ABS Cement Issue 12.07.12

## 15. Regulatory Information (continued)

#### **Guidance Notes**

Workplace Exposure Limits EH40 CHIP for everyone HSG(108) Introduction to Local Exhaust Ventilation HS(G)37

## 16. Other Information

Since the users working conditions are not known by us, the information supplied on this safety sheet is based on our current level of knowledge and on National and community regulations.

The product must not be used for any purpose other than those specified under heading 1 without first obtaining written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information given on this safety data sheet must be regarded as a description of the safety requirements relating to our product and not a guarantee of its properties.

MSDS 431.1 Page 7 of 7