Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Revision Date: 12/15/2014 Date of issue: 10/30/2014 Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Titanium and Titanium Alloys

Synonyms: Alloy #200; Alloy #900; Alloy #STAGCG57; Alloy #342; Alloy #2SA

1.2. Intended Use of the Product

Use of the Substance/Mixture: No use is specified.

1.3. Name, Address, and Telephone of the Responsible Party

Distributor

ThyssenKrupp Materials NA, Inc. 22355 W. Eleven Mile Road Southfield, Michigan 48034

TEL: 248-233-5713

1.4. Emergency Telephone Number Emergency Number : 248-233-5713

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Classification (GHS-US)

Not classified

2.2. Label Elements

GHS-US Labeling No labeling applicable

2.3. Other Hazards

This product is present in a massive form as an alloy. It does not present the same hazards when the individual components are in their powdered forms. The materials present in this product in their powdered forms present aquatic toxicity to the environment, pyrophoricity, flammability, self-heating capabilities, carcinogenicity, water reactivity, and acute toxicity. When processed or where dust is generated a combustible dust hazard may be present. Avoid generating dust, generating sparks, ignition sources, and take all precautions.

Inhalation of dusts and fumes can cause metal fume fever. Symptoms can include a metallic or sweet taste in the mouth, sweating, shivering, headache, throat irritation, fever, chills, thirstiness, muscle aches, nausea, vomiting, weakness, fatigue, and shortness of breath.

Under normal use and handling of the solid form of this material there are few health hazards. Cutting, welding, melting, grinding etc. of these materials will produce dust, fume or particulate containing the component elements of these materials. Exposure to the dust, fume or particulate of these materials may present significant health hazards. Exposure to dust or fume may cause irritation of the eyes, skin and respiratory tract. Fine particulates dispersed in air may present an explosion hazard.

2.4. Unknown Acute Toxicity (GHS-US) No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Titanium	(CAS No) 7440-32-6	30 - 60, 60	Flam. Sol. 1, H228
		- 99	
Vanadium	(CAS No) 7440-62-2	< 0.1, 0.1 -	Not classified
		1, 1 - 5, 5 -	
		10, 10 - 13	
Molybdenum	(CAS No) 7439-98-7	< 0.1, 0.1 -	Comb. Dust
		1, 1 - 5, 5 -	
		10, 10 - 12	
Chromium	(CAS No) 7440-47-3	< 0.1, 0.1 -	Comb. Dust
		1, 1 - 5, 5 -	

12/15/2014 EN (English US) 1/13

24

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

		10, 10 - 11	
Aluminum	(CAS No) 7429-90-5	< 0.1, 0.1 -	Comb. Dust
		1, 1 - 5, 5 -	Flam. Sol. 1, H228
		8	Water-react. 2, H261
Zirconium	(CAS No) 7440-67-7	< 0.1, 0.1 -	Flam. Sol. 1, H228
		1, 1 - 5, 5 -	
		6	
Tin	(CAS No) 7440-31-5	< 0.1, 0.1 -	Comb. Dust
		1, 1 - 5	
Iron	(CAS No) 7439-89-6	< 0.1, 0.1 -	Not classified
		1, 1 - 2	
Niobium	(CAS No) 7440-03-1	< 0.1, 0.1 -	Flam. Sol. 1, H228
		1, 1 - 2	
Tantalum	(CAS No) 7440-25-7	< 0.1, 0.1 -	Flam. Sol. 1, H228
		1	
Nickel	(CAS No) 7440-02-0	< 0.1, 0.1 -	Skin Sens. 1, H317
		0.8	Carc. 2, H351
			STOT RE 1, H372
			Aquatic Acute 1, H400
			Aquatic Chronic 3, H412

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

General: IF exposed or concerned: Get medical advice/attention. Never give anything by mouth to an unconscious person.

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Keep at rest and in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

Skin Contact: Cool skin rapidly with cold water after contact with molten product. Removal of solidified molten material from skin requires medical assistance. Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash with plenty of soap and water. Wash contaminated clothing before reuse. Obtain medical attention if irritation persists.

Eye Contact: Removal of solidified molten material from the eyes requires medical assistance. Immediately rinse with water for a prolonged period (at least 15 minutes) while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER/doctor/physician if you feel unwell.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Welding, cutting, or processing this material may release dust or fumes that are hazardous.

Inhalation: Inhalation of dusts and fumes can cause metal fume fever. Symptoms can include a metallic or sweet taste in the mouth, sweating, shivering, headache, throat irritation, fever, chills, thirstiness, muscle aches, nausea, vomiting, weakness, fatigue, and shortness of breath.

Skin Contact: May cause an allergic skin reaction. Dust from physical alteration of this product causes skin irritation. Causes severe skin burns. Contact with fumes or metal powder will irritate skin. Contact with hot, molten metal will cause thermal burns. Dust may cause irritation in skin folds or by contact in combination with tight clothing. Mechanical damage via flying particles and chipped slag is possible.

Eye Contact: Dust may cause mechanical irritation to eyes, nose, throat, and lungs.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

12/15/2014 EN (English US) 2/13

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Chronic Symptoms: In massive form, no hazard exists. If physically altered to present slivers, ribbons, dusts or fumes from molten material: Aluminum: Inhalation of finely divided aluminum powder may cause pulmonary fibrosis. Inhalation of iron oxide fumes undergoing decomposition may cause irritation and flu-like symptoms, otherwise iron oxide is not hazardous. Inhalation of Nickel compounds has been shown in studies to provide an increased incidence of cancer of the nasal cavity, lung and possibly larynx in nickel refinery workers. Nickel: May cause a form of dermatitis known as nickel itch and intestinal irritation, which may cause disorders, convulsions and asphyxia. Chromium: Certain hexavalent chromium compounds have been demonstrated to be carcinogenic on the basis of epidemiological investigations on workers and experimental studies in animals. Increased incidences of respiratory cancer have been found in chromium (VI) workers. There is an increased incidence of lung cancer in industrial workers exposed to chromium (VI) compounds. Please refer to IARC volume 23 for a more detailed discussion. Tin: Has been shown to increase incidence of sarcoma in animal tests. Chronic exposure to tin dusts and fume may result in "stannosis", a mild form of pneumoconiosis.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire. Dry sand; Class D Extinguishing Agent (for metal powder fires).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire. Do not use water when molten material is involved, may react violently or explosively on contact with water.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: A non-combustible material, not considered flammable but will melt above 1671.1 °C (3039.98 °F).

Explosion Hazard: In molten state: reacts violently with water (moisture). **Reactivity:** Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Exercise caution when fighting any chemical fire.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. **Hazardous Combustion Products:** Oxides of tin. Oxides of nickel. Chromium oxides. Oxides of carbon. Oxides of aluminum. Molybdenum oxides. Oxides of titanium.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not handle until all safety precautions have been read and understood. Do not breathe vapors from molten product.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain and collect as any solid.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. For particulates and dust: Avoid actions that cause dust to become airborne during clean-up such as dry sweeping or using compressed air. Use PPE described in Section 8. Vacuum must be fitted with HEPA filter to prevent release of particulates during clean-up.

6.4. Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

12/15/2014 EN (English US) 3/13

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: May generate flammable/explosive dusts or turnings when brushed, machined or ground. Use care during processing to minimize generation of dust. Where excessive dust may result, use approved respiratory protection equipment. Heating of product can release toxic or irritating fumes; ensure proper ventilation is employed, proper precautions are enforced, and applicable regulations are followed. Inhalation of fumes may cause metal fume fever.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a dry, cool and well-ventilated place.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Alkalis. Metal oxides. Water, humidity. Corrosive substances in contact with metals may produce flammable hydrogen gas.

7.3. Specific End Use(s)

No use is specified.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Vanadium (7440-62-2)		
USA OSHA	OSHA PEL (Ceiling) (mg/m³)	0.5 mg/m³ (respirable dust)
		0.1 mg/m³ (fume)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1 mg/m³
USA NIOSH	NIOSH REL (STEL) (mg/m³)	3 mg/m³
Molybdenum (7439-98-7)		
USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³ (inhalable fraction)
		3 mg/m³ (respirable fraction)
USA IDLH	US IDLH (mg/m³)	5000 mg/m³
Alberta	OEL TWA (mg/m³)	10 mg/m³ (total)
British Columbia	OEL TWA (mg/m³)	3 mg/m³ (respirable)
Manitoba	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)
Newfoundland & Labrador	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)
Nova Scotia	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)
Ontario	OEL TWA (mg/m³)	10 mg/m³ (metal-inhalable)
Prince Edward Island	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)
Saskatchewan	OEL STEL (mg/m³)	20 mg/m³ (inhalable fraction)
Saskatchewan	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)
Chromium (7440-47-3)		
Mexico	OEL TWA (mg/m³)	0.5 mg/m³
USA ACGIH	ACGIH TWA (mg/m³)	0.5 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	1 mg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.5 mg/m ³
USA IDLH	US IDLH (mg/m³)	250 mg/m³
Alberta	OEL TWA (mg/m³)	0.5 mg/m ³
British Columbia	OEL TWA (mg/m³)	0.5 mg/m³
Manitoba	OEL TWA (mg/m³)	0.5 mg/m ³
New Brunswick	OEL TWA (mg/m³)	0.5 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m³)	0.5 mg/m ³
Nova Scotia	OEL TWA (mg/m³)	0.5 mg/m ³
Nunavut	OEL STEL (mg/m³)	1.5 mg/m³

12/15/2014 EN (English US) 4/13

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Nunavut	OEL TWA (mg/m³)	0.5 mg/m ³
Northwest Territories	OEL STEL (mg/m³)	1.5 mg/m³
Northwest Territories	OEL TWA (mg/m³)	0.5 mg/m ³
Ontario	OEL TWA (mg/m³)	0.5 mg/m³
Prince Edward Island	OEL TWA (mg/m³)	0.5 mg/m³
Québec	VEMP (mg/m³)	0.5 mg/m³
Saskatchewan	OEL STEL (mg/m³)	1.5 mg/m³
Saskatchewan	OEL TWA (mg/m³)	0.5 mg/m ³
Yukon	OEL STEL (mg/m³)	3.0 mg/m ³
Yukon	OEL TWA (mg/m³)	0.1 mg/m³
Aluminum (7429-90-5)		
Mexico	OEL TWA (mg/m³)	10 mg/m³ (dust)
USA ACGIH	ACGIH TWA (mg/m³)	1 mg/m³ (respirable fraction)
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust)
	, , , ,	5 mg/m³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	10 mg/m³ (total dust)
		5 mg/m³ (respirable dust)
Alberta	OEL TWA (mg/m³)	10 mg/m³ (dust)
British Columbia	OEL TWA (mg/m³)	1.0 mg/m³ (respirable)
Manitoba	OEL TWA (mg/m³)	1 mg/m³ (respirable fraction)
New Brunswick	OEL TWA (mg/m³)	10 mg/m³ (metal dust)
Newfoundland & Labrador	OEL TWA (mg/m³)	1 mg/m³ (respirable fraction)
Nova Scotia	OEL TWA (mg/m³)	1 mg/m³ (respirable fraction)
Nunavut	OEL STEL (mg/m³)	20 mg/m ³
Nunavut	OEL TWA (mg/m³)	10 mg/m³
Northwest Territories	OEL STEL (mg/m³)	20 mg/m ³
Northwest Territories	OEL TWA (mg/m³)	10 mg/m³
Ontario	OEL TWA (mg/m³)	1 mg/m³ (respirable)
Prince Edward Island	OEL TWA (mg/m³)	1 mg/m³ (respirable fraction)
Québec	VEMP (mg/m³)	10 mg/m³
Saskatchewan	OEL STEL (mg/m³)	20 mg/m³ (dust)
Saskatchewan	OEL TWA (mg/m³)	10 mg/m³ (dust)
Zirconium (7440-67-7)		
USA ACGIH	ACGIH TWA (mg/m³)	5 mg/m³
USA ACGIH	ACGIH STEL (mg/m³)	10 mg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	5 mg/m³
USA NIOSH	NIOSH REL (STEL) (mg/m³)	10 mg/m³
USA IDLH	US IDLH (mg/m³)	50 mg/m³
Alberta	OEL STEL (mg/m³)	10 mg/m³
Alberta	OEL TWA (mg/m³)	5 mg/m³
British Columbia	OEL STEL (mg/m³)	10 mg/m³
British Columbia	OEL TWA (mg/m³)	5 mg/m³
Manitoba	OEL STEL (mg/m³)	10 mg/m³
Manitoba	OEL TWA (mg/m³)	5 mg/m³
New Brunswick	OEL STEL (mg/m³)	10 mg/m³
New Brunswick	OEL TWA (mg/m³)	5 mg/m³
Newfoundland & Labrador	OEL STEL (mg/m³)	10 mg/m³
Newfoundland & Labrador	OEL TWA (mg/m³)	5 mg/m³
Nova Scotia	OEL STEL (mg/m³)	10 mg/m³
Nova Scotia	OEL TWA (mg/m³)	5 mg/m³
Ontario	OEL STEL (mg/m³)	10 mg/m³

12/15/2014 EN (English US) 5/13

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

	,	
Ontario	OEL TWA (mg/m³)	5 mg/m³
Prince Edward Island	OEL STEL (mg/m³)	10 mg/m ³
Prince Edward Island	OEL TWA (mg/m³)	5 mg/m ³
Québec	VECD (mg/m³)	10 mg/m ³
Québec	VEMP (mg/m³)	5 mg/m ³
Saskatchewan	OEL STEL (mg/m³)	10 mg/m ³
Saskatchewan	OEL TWA (mg/m³)	5 mg/m ³
Tin (7440-31-5)		
Mexico	OEL TWA (mg/m³)	2 mg/m³
Mexico	OEL STEL (mg/m³)	4 mg/m³
USA ACGIH	ACGIH TWA (mg/m³)	2 mg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	2 mg/m³
USA IDLH	US IDLH (mg/m³)	100 mg/m³
Alberta	OEL TWA (mg/m³)	2 mg/m³
British Columbia	OEL TWA (mg/m³)	2 mg/m³
Manitoba	OEL TWA (mg/m³)	2 mg/m³
New Brunswick	OEL TWA (mg/m³)	2 mg/m³
Newfoundland & Labrador	OEL TWA (mg/m³)	2 mg/m³
Nova Scotia	OEL TWA (mg/m³)	2 mg/m³
Ontario	OEL TWA (mg/m³)	2 mg/m³
Prince Edward Island	OEL TWA (mg/m³)	2 mg/m³
Québec	VEMP (mg/m³)	2 mg/m³
Saskatchewan	OEL STEL (mg/m³)	4 mg/m³
Saskatchewan	OEL TWA (mg/m³)	2 mg/m³
Tantalum (7440-25-7)		
Mexico	OEL TWA (mg/m³)	5 mg/m³
Mexico	OEL STEL (mg/m³)	10 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	5 mg/m³ (dust)
USA NIOSH	NIOSH REL (STEL) (mg/m³)	10 mg/m³ (dust)
USA IDLH	US IDLH (mg/m³)	2500 mg/m³ (dust)
Alberta	OEL TWA (mg/m³)	5 mg/m³ (dust)
British Columbia	OEL TWA (mg/m³)	5 mg/m³
New Brunswick	OEL TWA (mg/m³)	5 mg/m³ (dust)
Nunavut	OEL STEL (mg/m³)	10 mg/m³
Nunavut	OEL TWA (mg/m³)	5 mg/m³
Northwest Territories	OEL STEL (mg/m³)	10 mg/m³
Northwest Territories	OEL TWA (mg/m³)	5 mg/m³
Québec	VEMP (mg/m³)	5 mg/m³ (dust)
Saskatchewan	OEL STEL (mg/m³)	10 mg/m³
Saskatchewan	OEL TWA (mg/m³)	5 mg/m³
Yukon	OEL STEL (mg/m³)	10 mg/m³
Yukon	OEL TWA (mg/m³)	5 mg/m³
Nickel (7440-02-0)		
Mexico	OEL TWA (mg/m³)	1 mg/m³
USA ACGIH	ACGIH TWA (mg/m³)	1.5 mg/m³ (inhalable fraction)
USA OSHA	OSHA PEL (TWA) (mg/m³)	1 mg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.015 mg/m³
USA IDLH	US IDLH (mg/m³)	10 mg/m³
Alberta	OEL TWA (mg/m³)	1.5 mg/m³
British Columbia	OEL TWA (mg/m ³)	0.05 mg/m³
Distribution Columbia	· · · · · · · · · · · · · · · · · ·	0.000/

12/15/2014 EN (English US) 6/13

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Manitoba	OEL TWA (mg/m³)	1.5 mg/m³ (inhalable fraction)
New Brunswick	OEL TWA (mg/m³)	1 mg/m³
Newfoundland & Labrador	OEL TWA (mg/m³)	1.5 mg/m³ (inhalable fraction)
Nova Scotia	OEL TWA (mg/m³)	1.5 mg/m³ (inhalable fraction)
Nunavut	OEL STEL (mg/m³)	2 mg/m³
Nunavut	OEL TWA (mg/m³)	1 mg/m³
Northwest Territories	OEL STEL (mg/m³)	2 mg/m³
Northwest Territories	OEL TWA (mg/m³)	1 mg/m³
Ontario	OEL TWA (mg/m³)	1 mg/m³ (inhalable)
Prince Edward Island	OEL TWA (mg/m³)	1.5 mg/m³ (inhalable fraction)
Québec	VEMP (mg/m³)	1 mg/m³
Saskatchewan	OEL STEL (mg/m³)	3 mg/m³ (inhalable fraction)
Saskatchewan	OEL TWA (mg/m³)	1.5 mg/m³ (inhalable fraction)
Yukon	OEL STEL (mg/m³)	3 mg/m³
Yukon	OEL TWA (mg/m³)	1 mg/m³

8.2. Exposure Controls

Appropriate Engineering Controls: Use local exhaust or general dilution ventilation or other suppression methods to maintain dust levels below exposure limits. Power equipment should be equipped with proper dust collection devices. Ensure all national/local regulations are observed.

Personal Protective Equipment: Protective clothing. Gloves. Safety glasses. Dust formation: dust mask. Insufficient ventilation: wear respiratory protection.











Materials for Protective Clothing: Chemically resistant materials and fabrics. With molten material wear thermally protective clothing.

Hand Protection: Wear chemically resistant protective gloves. If material is hot, wear thermally resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing. Wash contaminated clothing before reuse.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State: SolidAppearance: MetallicOdor: OdorlessOdor Threshold: Not availablepH: Not availableEvaporation Rate: Not available

Melting Point : 1537.8 - 1671.1 °C (2800.04 - 3039.98 °F)

Freezing Point Not available **Boiling Point** Not available **Flash Point** Not applicable **Auto-ignition Temperature** Not available **Decomposition Temperature** Not available Flammability (solid, gas) Not available **Lower Flammable Limit** Not available **Upper Flammable Limit** Not available **Vapor Pressure** Not available

12/15/2014 EN (English US) 7/13

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Relative Vapor Density at 20 °C : Not available Relative Density : Not available

Specific Gravity : 4.5

Solubility: Insoluble in waterPartition Coefficient: N-octanol/water: Not availableViscosity: Not available

Explosion Data – Sensitivity to Mechanical Impact : Not expected to present an explosion hazard due to mechanical impact.

Explosion Data – Sensitivity to Static Discharge : Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity: Hazardous reactions will not occur under normal conditions.

- **10.2.** Chemical Stability: Stable under recommended handling and storage conditions (see section 7).
- **10.3.** Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
- **10.4. Conditions to Avoid:** Avoid creating or spreading dust. Sparks, heat, open flame and other sources of ignition.
- **10.5. Incompatible Materials:** When molten: water. Strong acids, strong bases, strong oxidizers. Alkalis. Metal oxides. Moisture. Corrosive substances in contact with metals may produce flammable hydrogen gas.
- **10.6. Hazardous Decomposition Products:** Inhalation of fumes may cause metal fume fever. Oxides of iron and carbon. Organic acid vapors. Chromium (VI) compounds. Oxides of titanium.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity: Not classified
LD50 and LC50 Data: Not available
Skin Corrosion/Irritation: Not classified
Serious Eye Damage/Irritation: Not classified
Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified **Carcinogenicity:** Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Inhalation of dusts and fumes can cause metal fume fever. Symptoms can include a metallic or sweet taste in the mouth, sweating, shivering, headache, throat irritation, fever, chills, thirstiness, muscle aches, nausea, vomiting, weakness, fatigue, and shortness of breath.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction. Dust from physical alteration of this product causes skin irritation. Causes severe skin burns. Contact with fumes or metal powder will irritate skin. Contact with hot, molten metal will cause thermal burns. Dust may cause irritation in skin folds or by contact in combination with tight clothing. Mechanical damage via flying particles and chipped slag is possible.

Symptoms/Injuries After Eye Contact: Dust may cause mechanical irritation to eyes, nose, throat, and lungs.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: In massive form, no hazard exists. If physically altered to present slivers, ribbons, dusts or fumes from molten material: Aluminum: Inhalation of finely divided aluminum powder may cause pulmonary fibrosis. Inhalation of iron oxide fumes undergoing decomposition may cause irritation and flu-like symptoms, otherwise iron oxide is not hazardous. Inhalation of Nickel compounds has been shown in studies to provide an increased incidence of cancer of the nasal cavity, lung and possibly larynx in nickel refinery workers. Nickel: May cause a form of dermatitis known as nickel itch and intestinal irritation, which may cause disorders, convulsions and asphyxia. Chromium: Certain hexavalent chromium compounds have been demonstrated to be carcinogenic on the basis of epidemiological investigations on workers and experimental studies in animals. Increased incidences of respiratory cancer have been found in chromium (VI) workers. There is an increased incidence of lung cancer in industrial workers exposed to chromium (VI) compounds. Please refer to IARC volume 23 for a more detailed discussion. Tin: Has been shown to increase incidence of sarcoma in animal tests. Chronic exposure to tin dusts and fume may result in "stannosis", a mild form of pneumoconiosis.

12/15/2014 EN (English US) 8/13

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Molybdenum (7439-98-7)	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
Chromium (7440-47-3)	
LD50 Oral Rat	> 5000 mg/kg
Tin (7440-31-5)	
LD50 Oral Rat	700 mg/kg
Niobium (7440-03-1)	
LD50 Oral Rat	> 10 g/kg
Nickel (7440-02-0)	
LD50 Oral Rat	> 9000 mg/kg
Chromium (7440-47-3)	
IARC Group	3
Nickel (7440-02-0)	
IARC Group	2B
National Toxicity Program (NTP) Status	Reasonably anticipated to be Human Carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity No additional information available

Nickel (7440-02-0)	
LC50 Fish 1	100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)
EC50 Daphnia 1	13 (13 - 200) μg/l (Exposure time: 48h - Species: Ceriodaphnia dubia [static])
LC 50 Fish 2	1.3 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])
EC50 Daphnia 2	1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 Other Aquatic Organisms 2	0.174 (0.174 - 0.311) mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata
	[static])

Persistence and Degradability

Titanium and Titanium Alloys	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Titanium and Titanium Alloys	
Bioaccumulative Potential	Not established.

12.4. Mobility in Soil Not available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Treatment Methods: Recycle product or dispose properly.

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

SECTION 14: TRANSPORT INFORMATION

14.1.	In Accordance with DOT	Not regulated for transport
14.2.	In Accordance with IMDG	Not regulated for transport
14.3.	In Accordance with IATA	Not regulated for transport
14.4.	In Accordance with TDG	Not regulated for transport

12/15/2014 EN (English US) 9/13

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations		
SECTION 15: REGULATORY INFORMATION		
15.1. US Federal Regulations		
Titanium and Titanium Alloys		
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard	
Titanium (7440-32-6)		
Listed on the United States TSCA (Toxic Substances Control Act)	inventory	
Vanadium (7440-62-2)		
Listed on the United States TSCA (Toxic Substances Control Act)	inventory	
Listed on United States SARA Section 313		
SARA Section 313 - Emission Reporting	1.0 % (except when contained in an alloy)	
Molybdenum (7439-98-7)		
Listed on the United States TSCA (Toxic Substances Control Act)	inventory	
Chromium (7440-47-3)		
Listed on the United States TSCA (Toxic Substances Control Act)	inventory	
Listed on United States SARA Section 313		
SARA Section 313 - Emission Reporting	1.0 %	
Aluminum (7429-90-5)		
Listed on the United States TSCA (Toxic Substances Control Act)	inventory	
Listed on United States SARA Section 313	Listed on United States SARA Section 313	
SARA Section 313 - Emission Reporting	1.0 % (dust or fume only)	
Zirconium (7440-67-7)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Tin (7440-31-5)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Iron (7439-89-6)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Niobium (7440-03-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Tantalum (7440-25-7)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Nickel (7440-02-0)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Listed on United States SARA Section 313		
RQ (Reportable Quantity, Section 304 of EPA's List of Lists):	100 lb (only applicable if particles are < 100 μm)	
SARA Section 313 - Emission Reporting	0.1 %	
15.2. US State Regulations		
Nickel (7440-02-0)		

13.2. O3 State Regulations		
Nickel (7440-02-0)		
U.S California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of	
	California to cause cancer.	
Titanium (7440-32-6)		
U.S New Jersey - Right to Know Hazardous Substance List		
Vanadium (7440-62-2)		
U.S Massachusetts - Right To Know List		
U.S New Jersey - Right to Know Hazardous Substance List		
U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List		
U.S Pennsylvania - RTK (Right to Know) List		
Molybdenum (7439-98-7)		
U.S Massachusetts - Right To Know List		

12/15/2014 EN (English US) 10/13

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Chromium (7440-47-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances
- U.S. Pennsylvania RTK (Right to Know) List

Aluminum (7429-90-5)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Zirconium (7440-67-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Tin (7440-31-5)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Tantalum (7440-25-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Nickel (7440-02-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances
- U.S. Pennsylvania RTK (Right to Know) List

15.3. Canadian Regulations

Titanium and Titanium Alloys	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

Titanium (7440-32-6)

Listed on the Canadian DSL (Domestic Substances List)

Vanadium (7440-62-2)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

Molybdenum (7439-98-7)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

Chromium (7440-47-3)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 0.1 %

12/15/2014 EN (English US) 11/13

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria	
Aluminum (7429-90-5)		
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)		
IDL Concentration 1 %		
WHMIS Classification	Class B Division 6 - Reactive Flammable Material	
	Class B Division 4 - Flammable Solid	
Zirconium (7440-67-7)		
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (I	ngredient Disclosure List)	
IDL Concentration 1 %		
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria	
Tin (7440-31-5)		
Listed on the Canadian DSL (,	
Listed on the Canadian IDL (I	ngredient Disclosure List)	
IDL Concentration 1 %		
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria	
Iron (7439-89-6)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Class B Division 4 - Flammable Solid	
Niobium (7440-03-1)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Class B Division 4 - Flammable Solid	
Tantalum (7440-25-7)		
Tantalum (7440-25-7) Listed on the Canadian DSL (Domestic Substances List)	
	·	
Listed on the Canadian DSL (·	
Listed on the Canadian DSL (Listed on the Canadian IDL (·	
Listed on the Canadian DSL (Listed on the Canadian IDL (I IDL Concentration 1 % WHMIS Classification Nickel (7440-02-0)	Uncontrolled product according to WHMIS classification criteria	
Listed on the Canadian DSL (Listed on the Canadian IDL (I IDL Concentration 1 % WHMIS Classification Nickel (7440-02-0) Listed on the Canadian DSL (Uncontrolled product according to WHMIS classification criteria Domestic Substances List)	
Listed on the Canadian DSL (Listed on the Canadian IDL (I IDL Concentration 1 % WHMIS Classification Nickel (7440-02-0) Listed on the Canadian DSL (Listed on the Canadian IDL (I	Uncontrolled product according to WHMIS classification criteria Domestic Substances List)	
Listed on the Canadian DSL (Listed on the Canadian IDL (I IDL Concentration 1 % WHMIS Classification Nickel (7440-02-0) Listed on the Canadian DSL (Uncontrolled product according to WHMIS classification criteria Domestic Substances List)	

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 12/15/2014

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Carc. 2	Carcinogenicity Category 2
Comb. Dust	Combustible Dust
Flam. Sol. 1	Flammable solids Category 1
Skin Sens. 1	Skin sensitization Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1

12/15/2014 EN (English US) 12/13

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Water-react. 2	Substances and mixtures which in contact with water emit flammable gases Category 2
H228	Flammable solid
	May form combustible dust concentrations in air
H261	In contact with water releases flammable gases
H317	May cause an allergic skin reaction
H351	Suspected of causing cancer
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H412	Harmful to aquatic life with long lasting effects

Party Responsible for the Preparation of This Document

ThyssenKrupp Materials NA, Inc. 22355 W. Eleven Mile Road Southfield, Michigan 48034

TEL: 248-233-5681

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2

12/15/2014 EN (English US) 13/13