



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** Zinc-It® Instant Cold Galvanize

**Other means of identification**

**Product code** 18413

**Recommended use** Metallic coating

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufactured or sold by:**

**Company name** CRC Industries, Inc.  
**Address** 885 Louis Dr.  
Warminster, PA 18974 US

**Telephone**

**General Information** 215-674-4300

**Technical Assistance** 800-521-3168

**Customer Service**

**24-Hour Emergency (CHEMTREC)** 800-272-4620

703-527-3887 (US)

703-527-3887 (International)

**Website** www.crcindustries.com

## 2. Hazard(s) identification

|                              |  |   |
|------------------------------|--|---|
| <b>Physical hazards</b>      | Flammable liquids  | Category 2                              |
|                              | Substances and mixtures which, in contact with water, emit flammable gases | Category 2                              |
| <b>Health hazards</b>        | Skin corrosion/irritation  | Category 2                              |
|                              | Serious eye damage/eye irritation  | Category 2A                             |
|                              | Carcinogenicity  | Category 2                              |
|                              | Specific target organ toxicity, single exposure                            | Category 3 respiratory tract irritation |
|                              | Specific target organ toxicity, repeated exposure                          | Category 2                              |
| <b>Environmental hazards</b> | Aspiration hazard  | Category 1                              |
|                              | Hazardous to the aquatic environment, acute hazard                         | Category 1                              |
|                              | Hazardous to the aquatic environment, long-term hazard                     | Category 1                              |
| <b>OSHA defined hazards</b>  | Not classified.  |   |

**Label elements**



**Signal word** Danger

**Hazard statement** Highly flammable liquid and vapor. In contact with water releases flammable gas. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs (ears) through prolonged or repeated exposure by inhalation. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

## Precautionary statement

### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not allow contact with water. Handle under inert gas. Protect from moisture. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not breathe vapor. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

### Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical attention. Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention. In case of fire: Do not use water. Collect spillage.

### Storage

Store in a dry place. Store in a closed container. Store in a well-ventilated place. Keep cool. Store locked up.

### Disposal

Dispose of contents/container in accordance with local/regional/national regulations.

### Hazard(s) not otherwise classified (HNOC)

None known.

### Supplemental information

2.35% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 14.53% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

## 3. Composition/information on ingredients

---

### Mixtures

| Chemical name                             | Common name and synonyms | CAS number | %       |
|---|--------------------------|------------|---------|
| Zinc, Elemental                           |                          | 7440-66-6  | 70 - 80 |
| Xylene                                    |                          | 1330-20-7  | 10 - 20 |
| Ethylbenzene                              |                          | 100-41-4   | 1 - 3   |
| Solvent naphtha (petroleum), light aliph. |                          | 64742-89-8 | 1 - 3   |

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

---

### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Call a POISON CENTER or doctor/physician if you feel unwell.

### Skin contact

Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages. Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

### Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

### Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

### Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

### General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

---

|  |  |
|--|--|
| <b>Suitable extinguishing media</b>                                  | Foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).  |
| <b>Unsuitable extinguishing media</b>                                | Water.   |
| <b>Specific hazards arising from the chemical</b>                    | Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Do not use water. Hydrogen gas may form producing an explosive environment. |
| <b>Special protective equipment and precautions for firefighters</b> | Self-contained breathing apparatus and full protective clothing must be worn in case of fire.  |
| <b>Fire-fighting equipment/instructions</b>                          | In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Do not get water inside container. Do not mix with acid or caustic materials.   |
| <b>General fire hazards</b>  | Highly flammable liquid and vapor. In contact with water releases flammable gas.   |

## 6. Accidental release measures

---

|  |   |
|--|---|
| <b>Personal precautions, protective equipment and emergency procedures</b> | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| <b>Methods and materials for containment and cleaning up</b>               | Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.<br><br>Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.  |
| <b>Environmental precautions</b>   | Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.  |

## 7. Handling and storage

---

|   |   |
|---|---|
| <b>Precautions for safe handling</b>                                | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from any possible contact with water, because of violent reaction and possible flash fire. Handle under inert gas. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. Use non-sparking tools and explosion-proof equipment. Do not breathe vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment. For product usage instructions, please see the product label. |
| <b>Conditions for safe storage, including any incompatibilities</b> | No Smoking in areas where this material is used. Keep containers closed and upright when not in use. If the painted surface is to be welded, use a fan across the work area to prevent fumes from rising to the welder's face. Pump air into welder's hood to provide positive air pressure to prevent fumes from getting to welder.<br><br>Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Keep container tightly closed. Store in a well-ventilated place. Never allow product to get in contact with water during storage. Store away from incompatible materials (see Section 10 of the SDS).  |

## 8. Exposure controls/personal protection

---

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components                  | Type | Value                            |
|-----------------------------|------|----------------------------------|
| Ethylbenzene (CAS 100-41-4) | PEL  | 435 mg/m <sup>3</sup><br>100 ppm |
| Xylene (CAS 1330-20-7)      | PEL  | 435 mg/m <sup>3</sup><br>100 ppm |

**US. ACGIH Threshold Limit Values**

| Components                  | Type | Value   |
|-----------------------------|------|---------|
| Ethylbenzene (CAS 100-41-4) | TWA  | 20 ppm  |
| Xylene (CAS 1330-20-7)      | STEL | 150 ppm |
|                             | TWA  | 100 ppm |

**US. NIOSH: Pocket Guide to Chemical Hazards**

| Components                  | Type | Value                 |
|-----------------------------|------|-----------------------|
| Ethylbenzene (CAS 100-41-4) | STEL | 545 mg/m <sup>3</sup> |
|                             | TWA  | 125 ppm               |
|                             |      | 435 mg/m <sup>3</sup> |
|                             |      | 100 ppm               |

**Biological limit values****ACGIH Biological Exposure Indices**

| Components                  | Value    | Determinant                                   | Specimen            | Sampling Time |
|-----------------------------|----------|---|---------------------|---------------|
| Ethylbenzene (CAS 100-41-4) | 0.15 g/g | Sum of mandelic acid and phenylglyoxylic acid | Creatinine in urine | *             |
| Xylene (CAS 1330-20-7)      | 1.5 g/g  | Methylhippuric acids                          | Creatinine in urine | *             |

\* - For sampling details, please see the source document.

**Appropriate engineering controls**

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection****Hand protection**

Wear protective gloves such as: Nitrile. Neoprene.

**Other**

Wear appropriate chemical resistant clothing.

**Respiratory protection**

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance****Physical state**

Liquid.

**Form**

Liquid.

**Color**

Gray.

**Odor**

Solvent.

**Odor threshold**

Not available.

**pH**

Not available.

**Melting point/freezing point**

-138.8 °F (-94.9 °C) estimated

**Initial boiling point and boiling range**

210 °F (98.9 °C)

**Flash point**

45 °F (7.2 °C) Tag Closed Cup

|   |                             |
|---|-----------------------------|
| Evaporation rate                                    | Slow.                       |
| Flammability (solid, gas)                           | Not available.              |
| <b>Upper/lower flammability or explosive limits</b> |                             |
| Flammability limit - lower (%)                      | 0.7 %                       |
| Flammability limit - upper (%)                      | 22.7 %                      |
| Vapor pressure                                      | 1.2 hPa estimated           |
| Vapor density                                       | > 1 (air = 1)               |
| Relative density                                    | 2.47                        |
| Solubility (water)                                  | Not available.              |
| Partition coefficient (n-octanol/water)             | Not available.              |
| Auto-ignition temperature                           | 810 °F (432.2 °C) estimated |
| Decomposition temperature                           | Not available.              |
| Viscosity (kinematic)                               | Not available.              |
| Percent volatile                                    | 58.1 %                      |

## 10. Stability and reactivity

|                                    |  |
|------------------------------------|--|
| Reactivity                         | The product is stable and non-reactive under normal conditions of use, storage and transport.                          |
| Chemical stability                 | Material is stable under normal conditions.  |
| Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use.  |
| Conditions to avoid                | Avoid heat, sparks, open flames and other ignition sources. Exposure to moisture. Contact with incompatible materials. |
| Incompatible materials             | Never add water to this product. Acids. Caustics. Oxidizing agents.  |
| Hazardous decomposition products   | Carbon oxides.   |

## 11. Toxicological information

### Information on likely routes of exposure

|              |  |
|--------------|--|
| Inhalation   | May cause damage to organs through prolonged or repeated exposure by inhalation. May cause irritation to the respiratory system. |
| Skin contact | Causes skin irritation.  |
| Eye contact  | Causes serious eye irritation.   |
| Ingestion    | Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.           |

|  |  |
|--|--|
| Symptoms related to the physical, chemical and toxicological characteristics | Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. |
|--|--|

### Information on toxicological effects

|                |   |
|----------------|---|
| Acute toxicity | May be fatal if swallowed and enters airways. May cause respiratory irritation. |
|----------------|---|

| Product                         | Species | Test Results  |
|---------------------------------|---------|---|
| Zinc-It® Instant Cold Galvanize |         |   |
| <b>Acute</b>                    |         |   |
| <b>Dermal</b>                   |         |   |
| LD50                            | Rabbit  | 28264 mg/kg estimated                                       |
| <b>Inhalation</b>               |         |   |
| LC50                            | Rat     | 27800 ppm, 4 hours estimated<br>151 mg/l, 4 hours estimated |
| <b>Oral</b>                     |         |   |
| LD50                            | Rat     | 2467 mg/kg estimated  |

\* Estimates for product may be based on additional component data not shown.

|  |  |
|--|--|
| <b>Skin corrosion/irritation</b>         | Causes skin irritation.  |
| <b>Serious eye damage/eye irritation</b> | Causes serious eye irritation.   |
| <b>Respiratory sensitization</b>         | Not a respiratory sensitizer.  |
| <b>Skin sensitization</b>                | This product is not expected to cause skin sensitization.  |
| <b>Germ cell mutagenicity</b>            | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| <b>Carcinogenicity</b>                   | Suspected of causing cancer.   |

**IARC Monographs. Overall Evaluation of Carcinogenicity**

|                             |   |
|-----------------------------|---|
| Ethylbenzene (CAS 100-41-4) | 2B Possibly carcinogenic to humans.                 |
| Xylene (CAS 1330-20-7)      | 3 Not classifiable as to carcinogenicity to humans. |

**US. National Toxicology Program (NTP) Report on Carcinogens**

Not available.

|   |   |
|---|---|
| <b>Reproductive toxicity</b>                              | Based on available data, the classification criteria are not met.   |
| <b>Specific target organ toxicity - single exposure</b>   | May cause respiratory irritation.   |
| <b>Specific target organ toxicity - repeated exposure</b> | May cause damage to organs (ears) through prolonged or repeated exposure by inhalation.   |
| <b>Aspiration hazard</b>                                  | May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death. |
| <b>Chronic effects</b>                                    | May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.         |

**12. Ecological information**

**Ecotoxicity** Very toxic to aquatic life with long lasting effects.

| Product                                | Species  | Test Results                     |
|--|--|----------------------------------|
| <b>Zinc-It® Instant Cold Galvanize</b> |  |                                  |
| <b>Aquatic</b>                         |  |                                  |
| Crustacea                              | EC50 Daphnia   | 3.8509 mg/l, 48 hours estimated  |
| Fish                                   | LC50 Fish  | 38.8988 mg/l, 96 hours estimated |
| <b>Components</b>                      |  |                                  |
| <b>Ethylbenzene (CAS 100-41-4)</b>     |  |                                  |
| <b>Aquatic</b>                         |  |                                  |
| <i>Acute</i>                           |  |                                  |
| Crustacea                              | EC50 Water flea (Daphnia magna)                          | 2.1 mg/l, 48 hours               |
| Fish                                   | LC50 Fathead minnow (Pimephales promelas)                | 12.1 mg/l, 96 hours              |
| <b>Xylene (CAS 1330-20-7)</b>          |  |                                  |
| <b>Aquatic</b>                         |  |                                  |
| Fish                                   | LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 9.5 - 19.2 mg/l, 96 hours        |
| <b>Zinc, Elemental (CAS 7440-66-6)</b> |  |                                  |
| <b>Aquatic</b>                         |  |                                  |
| Crustacea                              | EC50 Water flea (Daphnia magna)                          | 2.8 mg/l, 48 hours               |
| Fish                                   | LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 0.56 mg/l, 96 hours              |

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential**

|  |            |
|--|------------|
| <b>Partition coefficient n-octanol / water (log Kow)</b> |            |
| Ethylbenzene   | 3.15       |
| Xylene   | 3.12 - 3.2 |
| <b>Bioconcentration factor (BCF)</b>                     |            |
| Xylene   | 15         |

|                              |   |
|------------------------------|---|
| <b>Mobility in soil</b>      | No data available.  |
| <b>Other adverse effects</b> | No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component. |

### 13. Disposal considerations

---

|  |  |
|--|--|
| <b>Disposal of waste from residues / unused products</b> | If discarded, this product is considered a RCRA ignitable waste, D001. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations. |
| <b>Hazardous waste code</b>                              | D001: Waste Flammable material with a flash point <140 F   |
| <b>Contaminated packaging</b>                            | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.   |

### 14. Transport information

---

#### DOT

|                                     |   |
|-------------------------------------|---|
| <b>UN number</b>                    | UN1263  |
| <b>UN proper shipping name</b>      | Paint, Limited Quantity   |
| <b>Transport hazard class(es)</b>   |   |
| <b>Class</b>                        | 3   |
| <b>Subsidiary risk</b>              | -   |
| <b>Label(s)</b>                     | 3   |
| <b>Packing group</b>                | III   |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. |
| <b>Special provisions</b>           | B1, B52, IB3, T2, TP1, TP29   |
| <b>Packaging exceptions</b>         | 150   |
| <b>Packaging non bulk</b>           | 173   |
| <b>Packaging bulk</b>               | 242   |

#### IATA

|                                     |   |
|-------------------------------------|---|
| <b>UN number</b>                    | UN1263  |
| <b>UN proper shipping name</b>      | Paint, Limited Quantity   |
| <b>Transport hazard class(es)</b>   |   |
| <b>Class</b>                        | 3   |
| <b>Subsidiary risk</b>              | -   |
| <b>Packing group</b>                | III   |
| <b>Environmental hazards</b>        | No.   |
| <b>ERG Code</b>                     | 3L  |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. |
| <b>Other information</b>            |   |
| <b>Passenger and cargo aircraft</b> | Allowed.  |
| <b>Cargo aircraft only</b>          | Allowed.  |

#### IMDG

|                                     |   |
|-------------------------------------|---|
| <b>UN number</b>                    | UN1263  |
| <b>UN proper shipping name</b>      | PAINT or PAINT RELATED MATERIAL, LIMITED QUANTITY                       |
| <b>Transport hazard class(es)</b>   |   |
| <b>Class</b>                        | 3   |
| <b>Subsidiary risk</b>              | -   |
| <b>Packing group</b>                | III   |
| <b>Environmental hazards</b>        |   |
| <b>Marine pollutant</b>             | No.   |
| <b>EmS</b>                          | F-E, S-E  |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. |

### 15. Regulatory information

---

|                               |  |
|-------------------------------|--|
| <b>US federal regulations</b> | This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. |
|-------------------------------|--|

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**  
Not regulated.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**SARA 304 Emergency release notification**

Not regulated.

**US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance**

Ethylbenzene (CAS 100-41-4)

Xylene (CAS 1330-20-7)

Zinc, Elemental (CAS 7440-66-6)

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Ethylbenzene (CAS 100-41-4)

Listed.

Xylene (CAS 1330-20-7)

Listed.

Zinc, Elemental (CAS 7440-66-6)

Listed.

**CERCLA Hazardous Substances: Reportable quantity**

Ethylbenzene (CAS 100-41-4)

1000 LBS

Xylene (CAS 1330-20-7)

100 LBS

Zinc, Elemental (CAS 7440-66-6)

1000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Ethylbenzene (CAS 100-41-4)

Xylene (CAS 1330-20-7)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

**Food and Drug Administration (FDA)** Not regulated.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Section 311/312**

**Hazard categories**

Immediate Hazard - Yes

Delayed Hazard - Yes

Fire Hazard - Yes

Pressure Hazard - No

Reactivity Hazard - Yes

**SARA 302 Extremely hazardous substance**

No

**US state regulations**

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

Zinc, Elemental (CAS 7440-66-6)

Ethylbenzene (CAS 100-41-4)

Xylene (CAS 1330-20-7)

**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

**US. New Jersey Worker and Community Right-to-Know Act**

Ethylbenzene (CAS 100-41-4)

Xylene (CAS 1330-20-7)

Zinc, Elemental (CAS 7440-66-6)

**US. Massachusetts RTK - Substance List**

Ethylbenzene (CAS 100-41-4)

Xylene (CAS 1330-20-7)

Zinc, Elemental (CAS 7440-66-6)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Ethylbenzene (CAS 100-41-4)

Xylene (CAS 1330-20-7)

Zinc, Elemental (CAS 7440-66-6)

**US. Rhode Island RTK**

Ethylbenzene (CAS 100-41-4)

Xylene (CAS 1330-20-7)

Zinc, Elemental (CAS 7440-66-6)



**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Ethylbenzene (CAS 100-41-4)

Listed: June 11, 2004

**Volatile organic compounds (VOC) regulations****EPA**

**VOC content (40 CFR 51.100(s))** 20 %

**Architectural coatings (40 CFR 59, Subpt. D)** Compliant

**State**

**Architectural coatings** This product is regulated as an Architectural Coating for Metallic Pigmented Coatings. This product is not compliant to be sold for use in California. This product is compliant in all other states.

**VOC content** 493.7 g/l

**International Inventories**

| Country(s) or region        | Inventory name   | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia                   | Australian Inventory of Chemical Substances (AICS)                     | Yes                    |
| Canada                      | Domestic Substances List (DSL)   | Yes                    |
| Canada                      | Non-Domestic Substances List (NDSL)                                    | No                     |
| China                       | Inventory of Existing Chemical Substances in China (IECSC)             | Yes                    |
| Europe                      | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes                    |
| Europe                      | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                       | Inventory of Existing and New Chemical Substances (ENCS)               | No                     |
| Korea                       | Existing Chemicals List (ECL)  | Yes                    |
| New Zealand                 | New Zealand Inventory  | Yes                    |
| Philippines                 | Philippine Inventory of Chemicals and Chemical Substances (PICCS)      | Yes                    |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory                          | Yes                    |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision**

|                            |   |
|----------------------------|---|
| <b>Issue date</b>          | 08-24-2015  |
| <b>Prepared by</b>         | Allison Cho   |
| <b>Version #</b>           | 01  |
| <b>Further information</b> | Not available.  |
| <b>HMIS® ratings</b>       | Health: 2*<br>Flammability: 3<br>Physical hazard: 1<br>Personal protection: J |
| <b>NFPA ratings</b>        | Health: 2<br>Flammability: 3<br>Instability: 1<br>Special hazards: -W-        |

**NFPA ratings****Disclaimer**

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.